Engineering Specification

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative
Approvar	1 topi coci itativo

WCA-411-D

Back-to-Back Floor Mounted Lavatory Carrier with Concealed Arms

Specification

Watts WCA-411-D/WC back-to-back floor mounted concealed arm lavatory carrier with heavy gauge steel offset uprights with integral welded feet, adjustable epoxy coated cast iron arms with leveling screws and basin locking device, upper tie rod, and plated hardware.

Call customer service if you need assistance with technical details.

Options	
Suffix	Description
-M42	42" Long Carrier Leg
-M54	2" Chrome Plated Escutcheons, Single
-M55	4" Chrome Plated Escutcheons, Single
-M60	Knee-Operated Valve Support Plate, Single
-WC	Extended Arm (27" x 20" ADA)
-WLA	Waste Line Access


NOTICE


Anchor legs to concrete floor with minimum 1/2"(13) anchor bolts (by others).

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.







Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (800) 338-2581 • Watts.com **Canada:** T: (888) 208-8927 • Watts.ca **Latin America:** T: (52) 55-4122-0138 • Watts.com

ES-WD-WCA-411-D 2525 © 2025 Watts