# **Engineering Specification**

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

# **RD-200-CP-85**

## IRMA Roof Drain with 8"x8"

# **Promenade Top**

### Specification

Watts RD-200-CP-85 epoxy coated cast iron IRMA roof drain with flashing clamp, 4"(102) high stainless steel perforated extension, 8"x8"(203x203) square heel proof epoxy coated ductile promenade top and no hub (standard) outlet.

Suffix	Pipe Size Description	
2	2"(51) Pipe Size	
3	3"(76) Pipe Size	
4	4"(102) Pipe Size (NH Only)	

Suffix	Outlet Type Description	
NH	No Hub (MJ)	
Р	Push On	
Т	Threaded Outlet	
Χ	Inside Caulk	



Suffix	Options Description	
-1	All Nickel Bronze Top	
-5	Sediment Bucket	
-6	Vandal Proof Top	
-9	Hinged Grate	
-13	Galvanized	
-B	Sump Receiver	
-D	Underdeck Clamp	
-F	Deck Flange/Adj. Extension	
-SO	Side Outlet	

Optional Body Material Suffix Description				
-60	PVC Body w/Socket Outlet			
-61	ABS Body w/Socket Outlet			

Load Rating	Free Area Sq. In.	
MD*	41	

Deck Opening 10"(254) with sump receiver

1 25/32" (45)	8" (203)								
					7				
	777		٦Ľ	Î.					<b>Z</b>
	20	0	0	0		0	þ	ାଁ	
4 11/32"   (111)	0	0	0	0	0	0	þ	0	
(102)	0	0	0	0	0	0	þ		
<u> </u>	20	0	0	0	0	0	þ	o O	
_		MT.					7		223
Ī	[						Ų		
		<b>M</b>					777	Z	
Chart B						Ŕ	7		
ļ					 				
_ 1			<u> </u>			N			
	Pipe Size								

### NOTICE

The load classifications are in accordance with the American National Standards ASME A112.6.3 ASME Ratings are as follows:

\*MD - Safe Live Load 2000-4999 lbs.(900-2250 kg.) The above categories are given as a guide only. Please consult factory.

### NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (800) 338-2581 • F: (828) 248-3929 • Watts.com Canada: T: (888) 208-8927 • F: (905) 481-2316 • Watts.ca Latin America: T: (52) 55-4122-0138 • Watts.com

© 2021 Watts ES-WD-RD-200-CP-85 2140