Engineering Specification

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

CO-200-SX

Floor Cleanout with **Heavy Duty Square Top** Specification

Watts CO-200-SX epoxy coated cast iron floor cleanout with 5" x 5"(127x127) square adjustable gasketed heavy duty nickel bronze top, removable gas tight gasketed brass cleanout plug, and no hub (standard) outlet.

Call customer service if you need assistance with technical details.

Pipe Sizing		
Suffix	Description	
2	2"(51) Pipe Size	
3	3"(76) Pipe Size	
4	4"(102) Pipe Size	

Outlet Type		
Suffix	Description	
NH	No Hub (MJ)	
P	Push On	
X	Inside Caulk	

Options		
Suffix	Description	
-C	Membrane Clamp	
-6	Vandal Proof	
-13	Galvanized Body	

Optional Body Material		
Suffix	Description	
-60	PVC Body w/Poly Plug	
-61	ABS Body w/Poly Plug	

Load Rating	
HD	

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.






Chart A

Pipe Size	No Hub (MJ)	Push On	PVC/ABS
2"(51)	4 1/2"(114)	5 1/2"(140)	4"(102)
3"(76)	4 1/2"(114)	5 1/2"(140)	4"(102)
4"(102)	4 3/4"(121)	5 1/2"(140)	4"(102)

NOTICE

The load classifications are in accordance with the American National Standards ASME A112.21.1M ASME Ratings are as follows:

HD - Safe Live Load 5000-7499 lbs. (2250-3375 kg) The above categories are given as a guide only. Please consult factory.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

USA: T: (800) 338-2581 • Watts.com Canada: T: (888) 208-8927 • Watts.ca

Latin America: T: (52) 55-4122-0138 • Watts.com

ES-WD-CO-200-SX 2410

