_	
	,

OF240-4

6					
MODE					
MODEL NO.	ORDERING CODES (EDP NO.)	INLET	OUTLET	OVERALL HEIGHT (SEE NOTE 5)	
OF210-1	0002151	11.0	11.0	14.0	
OF220-2	0002152	21.1	21.1	24.3	

25.1

0002153 21.2 21.2

OTHERWISE NOTED & ARE ± 1 INCH (25MM). 2. ALL ITEMS SHOWN IN PHANTOM LINE ARE TO BE PROVIDED BY OTHERS. 3. ALL DIMENSIONS ARE SUBJECT TO CHANGE WITHOUT ANY

1. ALL DIMENSIONS SHOWN IN TABLE ARE IN INCHES, UNLESS

NOTICE.

NOTES:

D

 \rightarrow

- 4. INSTALL UNIONS FITTINGS ON INLET & OUTLET PLUMBING CONNECTIONS. 5. ALLOW A SPACE OF 3" MINIMUM BENEATH FILTER HOUSING FOR
- REMOVAL DURING FILTER CARTRIDGE REPLACEMENT. 6. FOR INSTALLATIONS USING METAL PLUMBING, CONNECT A
- METAL BONDING STRAP TO INLET & OUTLET METAL PLUMBING TO MAINTAIN ELECTRICAL CONTUNUITY. 7. THE FULL WEIGHT OF THE PIPING AND VALVES MUST BE
- SUPPORTED BY PIPE HANGERS OR OTHER MEANS.
- 8. INLET AND OUTLET HEADERS NEED TO BE SIZED ACCORDING TO FLOW RATE REQUIREMENTS BY OTHERS. 9. LIMIT INLET PRESSURE TO NOT EXCEED MAXIMUM PUBLISHED
- OPERATING PRESSURE. 10. WALL ANCHOR BOLTS TO BE PROVIDED BY OTHERS.









