

For Residential and Commercial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

LEAD FREE*

Poly-Alloy CrimpRing™ Adapters

Poly-Alloy CrimpRing™ Sweat Adapters are used to transition copper pipe to WaterPEX® supply lines. Threaded Adapters are used for the appropriate NPT fitting.

Specifications

System shall be plumbed using Watts WaterPEX® cross-linked polyethylene pipe. All joints shall be made using Watts brass CrimpRing™ and/or poly-alloy CrimpRing™ fittings using either the Watts copper CrimpRing™ or stainless steel CinchClamp™** crimping methods as outlined in the Watts WaterPEX® Installation Guidelines.

Installation Note

CrimpRing™ Adapters must be installed in accordance with all Watts WaterPEX® installation procedures, including information provided in WaterPEX® installation manual and guidelines.

Approvals



- Manufactured in accordance with American Society for Testing and Materials (ASTM) F-877 and F-2159
- Listed by the National Sanitation Foundation to NSF Standards 14 and 61 for use in potable water systems
- Listed by NSF to be in compliant to the Uniform Plumbing Code
- Labeled B137.5 which indicates that it is compliant to the CSA Standards B137.5
- Manufactured from Acudel® engineered thermoplastic resin.

*The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight.

**Note: Watts WaterPEX CinchClamp™ fittings should not be used with wrought copper PEX fittings.



WP12P
Crimp x MPT Threaded
Adapter

Warning!

If connections must be made in temperatures below 30°F, caution must be taken to allow the WaterPEX to form a proper seal against the barb. Apply the connection slowly to ensure the PEX material conforms to the barb.

Dimensions – Weights

MODEL	INLET			OUTLET			PKG. WEIGHT	
	<i>in.</i>	<i>mm</i>	<i>type</i>	<i>in.</i>	<i>mm</i>	<i>type</i>	<i>lbs.</i>	<i>kgs.</i>
CrimpRing™ Threaded Adapters — Crimp x Male								
WP12B-0808PB	½	15	Crimp Fitting	½	15	MPT	1	0.5
WP12B-0812PB	½	15	Crimp Fitting	¾	20	MPT	2	0.9
WP12B-1212PB	¾	20	Crimp Fitting	¾	20	MPT	2	0.9



A Watts Water Technologies Company

ES-WP-PAAdapters 1020



USA: 815 Chestnut St., No. Andover, MA 01845-6098; www.watts.com
Canada: 5435 North Service Rd., Burlington, ONT. L7L 5H7; www.wattscanada.ca

© 2010 Watts