

QXZQ.EX27072 Fire Pump Relief Valves

Page Bottom

Fire Pump Relief Valves

See General Information for Fire Pump Relief Valves

AMES FIRE & WATERWORKS

EX27072

1485 TANFORAN AVE WOODLAND, CA 95776-6108 USA

Models 920G-UL (globe body), 920A-UL (angle body) in 3, 4, 6 and 8 in. sizes, for use where the maximum relief pressure does not exceed 300 psi.

Model 920GF (globe body) with Class 150 Flange end configuration in the 1-1/2, 2, 2-1/2, 3, 4, 6 and 8 in. sizes, for use where the maximum relief pressure does not exceed 200 psi.

Model 920GF (globe body) with Class 150 Flange end configuration in the 1-1/2, 2, 2-1/2, 3, 4, 6 and 8 in. sizes, for use where the maximum relief pressure does not exceed 200 psi.

Model 920GF (globe body) with Class 300 Flange end configuration in the 2, 2-1/2, 3, 4, 6 and 8 in. sizes, for use where the maximum relief pressure does not exceed 300 psi.

Model 920AF (angle body) with Class 150 Flange end configuration in the 2, 2-1/2, 3, 4, 6 and 8 in. sizes, for use where the maximum relief pressure does not exceed 200 psi.

Model 920AF (angle body) with Class 300 Flange end configuration in the 2-1/2, 3, 4, 6 and 8 in. sizes, for use where the maximum relief pressure does not exceed 300 psi.

Model 920AF (angle body) with Class 300 by Class 150 Flange end configuration in the 3, 4, 6 and 8 in. sizes, for use where the maximum relief pressure does not exceed 300 psi.

End configurations shall be installed on systems not exceeding the end configurations working capabilities.

Last Updated on 2016-12-16

Questions? Print this page Terms of Use Page Top

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".

1 of 1 9/6/17, 10:04 AM