Engineering Specification

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

Cast Carbon & Alloy Steel Flanged & Butt Weld End Y Strainers

Models: 782*, Class 300 782-WE*, Class 300 Sizes: 1/2"- 24" (15 - 600mm)

* The 782/782-WE supersede model 762/762-WE. Model 762/762-WE available upon request

Typical Service

- Used extensively to strain foreign matter from pipelines and provide economical protection for costly pumps, meters, valves, and other similar mechanical equipment.
- Especially important where weld debris is likely present in the pipeline.
- Well suited for long service in high pressure and temperature applications.

Features

 Machined seats in both body and cap align and lock the screen in place to stop sediment bypass. Machined seats facilitate alignment and accurate reseating after servicing.

Construction

- Designed for Class 300 specifications.
- Heavy gauge reinforced screens are used.
- IMPORTANT NOTE:
 - Model 782-WE ends are machined to match Schedule 40 pipe.
 - Other connections are available, consult factory.

Self-Cleaning

• Self-cleaning is accomplished by opening the plug or valve connected to the blowoff outlet.


Blowoff Outlets

- Blowoff outlets are NPT tapped at location C. See next page for NPT sizes.
- Blind covers are available, consult factory.

Capacity

- Generously proportioned bodies.
- Open Area Ratio much greater than pipe size, ensuring low pressure drop.

Mueller Steam Specialty product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Mueller Steam Specialty Technical Service. Mueller Steam Specialty reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Mueller Steam Specialty products previously or subsequently sold.



Pressure/Temperature–Non-Shock Model Material Rating 782, Carbon Steel 740psi @ -20°F to 100°F 782WE 51.02 bar @ 37.78°C 300psi @ 850°F 20.86 bar @ 454.44°C 782. Chrome-Molv 750psi @ -20°F to 100°F 782WE 51.71 bar @ 37.78°C 485psi @ 850°F 33.44 bar @ 454.44°C

Screens

		STANDARD) (WATER)	STEAM RECOMENDATION		
MODEL	SIZES	MATERIAL	OPENING	MATERIAL	OPENING	
All	1⁄2" - 4"	304SS	.062 perf	304SS	.033 perf	
All	5" - 12"	304SS	.062 perf	304SS	.045 perf	
All	14" and Up	304SS	.125 perf	304SS	.062 perf	

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.



A WATTS Brand

Material

	782, 782-WE						
Body	Carbon Steel, ASTM A216 Grade WCB						
Cover	Carbon Steel, ASTM A216 Grade WCB						
Gasket	316SS Tang Graphite						

ALSO AVAILABLE:


Body/Cap: Carbon-Moly ASTM A217 Gr. W1, Chrome-Moly ASTM A217 Gr. WC6, Chrome-Moly ASTM A217 Gr. WC9


Pressure Drop

• See Pressure Drop Charts in Technical Data Section of the Mueller Steam Specialty Engineering binder.

Dimensions and Weights

SI	ZE				DIMEN	SIONS				WEI	GHT
		4	A	E)	1)		
		-	-	-	-	(N	PT)	Screen I	Removal		
in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kgs.
782											
1/2	15	61/8	155	31/2	89	3/8	10	5	130	5.5	2.5
3⁄4	20	7 ³ /4	197	3 ³ ⁄4	95	1/2	15	5	130	12.3	5.5
1	25	71/8	200	33/4	95	1/2	15	5	130	13	5.9
11/4	32	71/2	191	43⁄4	121	1/2	15	8	203	18.3	8.2
1½	40	81/4	210	43⁄4	121	1/2	15	8	203	18	8.1
2	50	85/8	219	51/4	133	1/2	15	7	178	22	10
2 ¹ / ₂	65	105/8	269	61/2	165	1	25	9 ³ ⁄ ₄	248	32	14.5
3	80	12	305	7	178	1	25	10	254	49	22
4	100	14½	368	81/4	210	1½	40	12	305	90	40
5	125	19 ⁵ ⁄16	491	131/2	343	2	50	20	508	120	54.5
6	150	19 ⁵ ⁄16	491	131/2	343	2	50	20	508	175	79
8	200	233/8	594	153⁄4	400	2	50	22 ³ / ₄	578	300	136
10	250	273/8	695	181/2	470	2	50	28	711	440	200
12	300	32	813	221/4	565	2	50	30	762	650	295
14	350	36	914	25	635	2	50	36½	927	1365	619
16	400	4 ¹¹ / ₁₆	1056	26 ½	673	2	50	42	1067	1936	878
18	450	46	1168	347/8	886	2	50	50%	1292	2576	1168
20	500	49 ½	1257	39	991	2	50	55%	1407	3111	1411
24	600	583/8	1483	44 ¹ / ₁₆	1119	2	50	671/4	1708	5305	2406
782-WI	E										
1/2	15	65/8	168	31/2	89	3/8	10	5	130	3	1.3
3/4	20	8 ⁵ /16	211	3 ³ ⁄4	95	1/2	15	5	130	9	4
1	25	8 ⁵ /16	211	33⁄4	95	1/2	15	5	130	9	4
11/4	32	101/8	260	51/4	133	1/2	15	8	203	12	5.4
1½	40	101/4	279	51/4	133	1/2	15	8	203	13	5.9
2	50	85/8	219	51/4	133	1/2	15	7	178	10	4.5
2 ¹ / ₂	65	10%	269	61/2	165	1	25	9 ³ ⁄ ₄	248	14	6.3
3	80	12	305	7	178	1	25	10	254	20	9
4	100	14½	368	81/4	210	1½	40	12	305	40	18
5	125	16¾	416	111/4	286	2	50	20	508	80	36
6	150	19 ⁵ ⁄16	491	131/2	343	2	50	20	508	90	40
8	200	233/8	594	15¾	400	2	50	223/4	578	168	76
10	250	273/8	695	181/2	470	2	50	28	711	250	113
12	300	32	813	221/4	565	2	50	30	762	440	200
14	350	36	416	25	635	2	50	361/2	927	1033	468
16	400	41 ³ ⁄ ₄	1060	261/2	673	2	50	42	1067	1520	639
18	450	46	1168	347/8	886	2	50	50%	1292	2060	934
20	500	491/2	1257	39	991	2	50	55%	1407	2471	1120
24	600	58 ½	1486	44 ¹ / ₁₆	1119	2	50	671/4	67¼	4500	2040





Apply For Certified Drawings.

Limited Warranty: Mueller Steam Specialty warrants each product to be free from defects in material and workmanship under normal usage for a period of one year from the date of original shipment. In the event of such defects within the warranty period, the Company will, at its option, replace or recondition the product without charge. This shall constitute the sole and exclusive remedy for breach of warranty, and the Company shall not be responsible for any incidental, special or consequential damages, including without limitation, lost profits or the cost of repairing or replacing other property which is damaged if this product does not work properly, other costs resulting from labor charges, delays, vandalism, negligence, fouling caused by foreign material, damage from adverse water conditions, chemical, or any other circumstances over which the Company has no control. This warranty shall be invalidated by any abuse, misuse, misuse, misupplication or improper installation of the product. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTES, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Any implied warranties that are imposed by law are limited in duration to one year.

Some States do not allow limitations on how long an implied warranty lasts, and some States do not allow the exclusion or limitation of incidental or consequential damages. Therefore the above limitations may not apply to you. This Limited Warranty gives you specific legal rights, and you may have other rights that vary from State to State. You should consult applicable state laws to determine your rights.



A WATTS Brand