# For Residential and Commercial Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No
Approval	Representative

# **Mixing Control 356**

# Dimensions: 4-3/4" H x 2-7/8" W x 1-7/8" D (120 x 74 x 48 mm)

The Mixing Control 356 is designed to operate a mixing pump to control the temperature in a hot water heating system using Outdoor Temperature Reset. It can be used in applications ranging from in-floor radiant to commercial baseboard systems for boiler protection with full reset. This control regulates a single heating water temperature through Outdoor Temperature Reset. It provides mixing by speeding up or slowing down a single permanent capacitor (standard wet rotor) circulator.



Mixing Control 356

#### Mixing Control 356

DESCRIPTION	PROPERTY
Literature	IOM-WR-Mixing Control 356, ES-WR-Mixing Control 356
Control	Microprocessor control. This is not a safety (limit) control
Packaged weight	1.5 lb. (670 g)
Dimensions	4-3/4" H x 2-7/8" W x 1-7/8" D (120 x 74 x 48 mm)
Enclosure	White PVC plastic, NEMA type 1
Approvals	CSA C US, meets class B: ICES & FCC Part 15
Ambient conditions	Indoor use only, 32 to 104°F (0 to 40°C), RH ≤90% Non-condensing
Power supply	24 V (ac) ±10%, 50/60 Hz, 3 VA
Var. pump	120 V (ac) 2.4 A, 1/6 hp
Relays	120 V (ac) 5 A, 1/6 hp
Mixing demand	24 V (ac) 2 VA
Sensors	NTC thermistor, 10 kΩ @ 77°F (25°C ±0.2°C) β=3892
-Included	Outdoor Sensor 070 and 2 of Universal Sensor 082

# Features

- Outdoor temperature reset
- Warm weather shut down
- Boiler control
- Automatic boiler differential
- Variable speed pump control



Side View

# Back View



Designed to mount on 2" x 4" electrical box





Watts Radiant product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Radiant Technical Service. Watts Radiant reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts Radiant products previously or subsequently sold.

A Watts Water Technologies Company

USA: Springfield, MO • Tel. (800) 276-2419 • Fax: (417) 864-8161 • www.wattsradiant.com Canada: Burlington, ONT. • Tel. (905) 332-4090 • Fax: (905) 332-7068 • www.watts.ca