Engineering Specification

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

FD-1190-PR-60

PVC Adjustable Floor Drain with Integrated Level

Specification

Watts Pronto!® FD-1190-PR-60 PVC floor drain with anchor flange, reversible clamping collar with primary and secondary weepholes, post-pour adjustable round heel proof stainless steel strainer with integrated bubble level, leveling shims, and PVC socket outlet.

Call customer service if you need assistance with technical details.

Chart A

Size

5"(127)

6"(152)

7"(178)

8"(203)

Min.

2 1/2"(64)

2 1/2"(64)

2 5/8"(67)

2 3/4"(70)

Max.

4 1/4"(108)

4 1/4"(108)

4 3/8"(111)

4 1/2"(114)

Pipe Sizing			
Suffix	Description		
2	2"(51) Pipe Size		
3	3"(76) Pipe Size		
4	4"(102) Pipe Size		

	Strainer	
Suffix	Description	
PR5	5"(127) Dia., Stainless Steel	
PR6	6"(152) Dia., Stainless Steel	
PR7	7"(178) Dia., Stainless Steel	

8"(203) Dia., Stainless Steel

PR8

Options		
Suffix	Description	
-6	Vandal Proof	
-7	Trap Primer Tapping	
-8	Backwater Valve (2, 3, 4" Only)	
-F4-50	4" Round Cast Iron Funnel	
-F4-1	4" Round Nickel Bronze Funnel	
-F6-1	6" Round Nickel Bronze Funnel	
-G-50	4" x 9" Oval Cast Iron Funnel	
-G-1	4" x 9" Oval Nickel Bronze Funnel	



Free Area Sq. In.

6

11

13

19

Rating


MD


LD

LD

MD







The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

WATTS

USA: T: (800) 338-2581 • Watts.com **Canada:** T: (888) 208-8927 • Watts.ca

Latin America: T: (52) 55-4122-0138 • Watts.com

ES-WD-FD-1190-PR-60 2433 © 2024 Watts